

<b>MARUTHI SOLAR SYSTEM, BANGALORE INDIA</b>					
<b>Department</b>	<b>Solar Energy</b>			<b>Form No.</b>	
<b>Title</b>	Specification For SSL LED Luminarie 4.5 W				
<b>Date</b>		<b>Rev. No.</b>	00	<b>Page No.</b>	1 of 2

**SPECIFICIATION NO:**

<b>Sr. No.</b>	<b>Parameter</b>	<b>Value</b>
<b>1</b>	<b>General</b>	
1.1	Application	Solar PV Street Light systems, RV systems, Village electrification, standby light source
1.2	Use	Outdoor
1.3	Lamp Type	White color LED
1.4	Lamp Wattage	4.5 W
1.5	Rated Light output (Lux)	10 LUX when measured at 4 meter diameter from a height of 4 meter. LED lamp 140 lum/watt
1.6	Lamp color temperature	5500-6500° K),
1.7	LED viewing angle	2x 60°
1.8	Rated Lamp life (Average)	>50000 Hrs
1.9	Light output degradation after 500 Hours ON continuous	< 10%
1.10	Humidity	95%RH
1.11	Storage Temperature	-20 to +70°C
1.12	Operating Temperature	0 to +50°C
<b>2</b>	<b>Electrical</b>	
2.1	Rated working voltage	12V DC
2.2	Working voltage range	10.5 to 14.4V DC
2.3	Driver type	PWM high efficient driver
2.5	Driver efficiency	> 80%
2.9	Lamp power (Input power)	6 Watts
2.10	Current consumption @12VDC Input	0.5 A ± 10%
2.11	Reverse Battery protection	Provided with fuse
2.12	Overload protection	Provided with fuse
2.13	Open Circuit Protection	Provided
2.14	Dusk to Down Protection	Provided
2.15	Solar charging Current	6A (Max)
2.16	Regulator Type	PWM Series Regulator

	<b>Prepared by</b>	<b>Verified by</b>	<b>Approved by</b>
<b>Signature</b>			
<b>Date</b>			

<b>MARUTHI SOLAR SYSTEM, BANGALORE INDIA</b>					
<b>Department</b>	<b>Solar Energy</b>			<b>Form No.</b>	
<b>Title</b>	Specification For SSL LED Luminarie 4.5 W				
<b>Date</b>		<b>Rev. No.</b>	00	<b>Page No.</b>	2 of 2

2.17	Self Consumption	< 10 mA (With no LED glowing)
2.18	Low Cut off Voltage	10.8V(+/-0.2V)
2.19	Reconnect Voltage	12.5V(+/-0.2V)
2.20	High voltage boost voltage	15.0V(+/-0.2V)
2.21	High voltage float level	14.5V(+/-0.2V)
2.22	Battery Low indication	Red LED
2.23	Battery charging indication	Green LED
2.24	Reverse blocking protection from battery to Array during night	Provided
2.25	Temperature compensation	Provided
<b>3</b>	<b>Mechanical</b>	
3.1	Enclosure	Pole mounting with screws & diameter should be 34mm,CF Lamp in base up configuration
3.3	Case	Injection Molded Engineering Nylon back. Fire Retardant grade or Aluminum casing with reflector o back
3.4	Light Diffuser	UV stabilized / Poly carbonate type front cover.
3.5	Reflector	Highly reflective anodized aluminum
3.6	Color (case)	Black color/ suitable color
3.8	Ingress Protection	IP 54

	<b>Prepared by</b>	<b>Verified by</b>	<b>Approved by</b>
<b>Signature</b>			
<b>Date</b>			